In Between ^{SK1 & SK2} Sami Kallio 2013





Product Fact Sheet



In Between ^{SK1} Sami Kallio 2013

Product category Chair

Environment Indoor

Production process

The legs and the armrest are turned from solid oak and the seat and side panels are formpressed from oak or ash veneer.

Material

Solid wood and formpressed veneer. This product has not been treated with any biocides.

Wood finishes

Oiled oak Smoked oiled oak Black lacquered oak Oiled walnut

Certifications

FSC Mix (C154398): Oiled Oak, Smoked Oiled Oak, Black Lacquered Oak




Strength, Durability and Safety Testing

The chair is tested for strength, durability and safety according to EN 15373 Level 2 - General contract use.

Related products



Dimensions





&Tradition®



Product: 7.0 kg / Incl. packaging: 14.5 kg

Produced in Latvia by Kvist Industries A/S

Please click here to download our Material Care

Felt gliders installed as standard.

Package dimensions

H: 95.0cm/37.4in W: 72.0cm/28.3in D: 60cm / 23.6in

Colli quantity

2

Weight

Gliders

Manufacturer

Cleaning Instructions

& Cleaning Instructions.

In Between SK1 Sami Kallio 2013

Wood finishes









Oiled oak

Smoked oiled oak

Black lacquered oak

Oiled walnut

Stock item









 \rightarrow Oiled walnut

 \rightarrow Oiled oak

 \rightarrow Smoked oiled oak

&Tradition[®]



In Between ^{SK2} Sami Kallio 2013

Product category Chair

Environment Indoor

Production process

The legs and the armrest are turned from solid oak and the seat and side panels are formpressed from oak or ash veneer.

Material

Solid wood, formpressed veneer, HR foam, fabric or leather upholstery. This product has not been treated with any biocides.

Wood finishes

Oiled oak Smoked oiled oak Black lacquered oak Oiled walnut

Certifications

FSC Mix (C154398): Oiled Oak, Smoked Oiled Oak, Black Lacquered Oak




Strength, Durability and Safety Testing The chair is tested for strength, durability and safety according to EN 16139 Level 1 - General contract use.

Related products







&Tradition®



Product: 7.0 kg / Incl. packaging: 14.5 kg

Fabric usage: 0.36 meter based on a 140 cm roll.

COM must be approved by &tradition to ensure suitability for upholstery on the chair.

Please click here to download our Material Care

Produced in Latvia by Kvist Industries A/S

Felt gliders installed as standard.

COM - Material Consumption

Leather usage: 0.36 sqm.

Manufacturer

Cleaning Instructions

& Cleaning Instructions.

Package dimensions

H: 80.0cm/31.5in W: 56.0cm/22in D: 59cm / 23.2in

Colli quantity

2

Weight

Gliders

In Between SK2 Sami Kallio 2013

Wood finishes







Black lacquered oak



Oiled walnut *Lead time: 6-8 weeks

Stock item





→ Smoked oiled oak w. Black silk leather



Smoked oiled oak



 \rightarrow Oiled oak w. Fiord 251



w. Cognac silk leather



→ Black Lacquered oak w. Fiord 191



→ Black Lacquered oak w. Black silk leather

* All other fabrics or leathers available with a lead time of 6-8 weeks.

& Tradition[®]





→ Smoked oiled oak w. Fiord 171



 \rightarrow Oiled oak



Recycling & Disassembly

In Between SK1 & SK2

RECYLING


The In Between chair is built to last, and we hope that your In Between will serve you for many years. The chair is made from solid wood and wood veneer, and can be easily separated from its base. All metal and wooden parts can be separated and delivered to a suitable recycling station.

SPARE PARTS

To purchase spare parts for your In Between chair, please write to our sales support team at info@andtradition.com with your query.

5 YEAR WARRANTY


&Tradition provides a 5-year warranty with every In Between chair, which covers faults which were present at the time of purchase, or which have occurred as a result of a manufacturing defect. The warranty is valid from the date stated on the original invoice.



DISASSEMBLY

Disassembling of In Between chair

- 1. To disassemble the In Between chair use an Allen key to loosen the screws holding the veneer panel in place.
- 2. Remove the veneer panel and unscrew the two screws located at the back of the seat.
- 3. Remove the gliders.



Disassembling of upholstered seat (SK2 only)

- 1. Unscrew the screws underneath the seat and remove the textile, padding and bushing from the wooden base of the seat.
- 2. Remove the textile, padding and bushing from the wooden base of the seat.

& Tradition®