Above

The fixture emits soft comfortable downlight. The conical shape and the matt, white-painted inside help assure even distribution of the light. The opening in the top of the fixture provides decorative illumination of the arch above, and ensures that the fixture retains the full expression of its visual shape both when illuminated and when switched off.





Set location: Alpha Dominche



Product info

Information

 \emptyset 400 & 550 LED: Compatible with leading and trailing edge mains dimmers. Please note that low power consumption on some products can affect dimming properties. \emptyset 400 & 550 LED variants are delivered with antiglare shade included. For all other variants the antiglare shade can be purchased as an accessory.

Mountine

Suspension type: Cable 2x0,75mm² (Ø175/250) Cable 2x1,00mm² (Ø400 E27) Cable 2x1,5mm² (Ø400 LED). Cable 2x0,75mm² with wire (Ø550). Canopy: Yes. LED canopy contains driver. Cable length: 3m (Ø175/250/400 (E27)), 4m (Ø400 (LED)/Ø550).

Finish

White, matt or Black, matt, wet painted.

Materials

Shade: Spun aluminium.

Sizes and weights

Width x Height x Length (mm) | $550 \times 660 \times 550 \text{ Max} = 5.4 \text{ kg} = 175 \times 210 \times 175 \text{ Max} = 0.6 \text{ kg} = 250 \times 300 \times 250 \text{ Max} = 1.0 \text{ kg} = 400 \times 480 \times 400 \text{ Max} = 4.0 \text{ kg} = 1.0 \times 100 \times 100$

Class

Ingress protection IP20. Electric shock protection II w/o ground (E27). Electric shock protection I w. ground. (LED)

Light source

1x60W E27

Information

 $\emptyset400$ & 550 LED: Compatible with leading and trailing edge mains dimmers. Please note that low power consumption on some products can affect dimming properties.

Ø400 & 550 LED variants are delivered with antiglare shade included. For all other variants the antiglare shade can be purchased as an accessory.

Ø 175/250/400/550

Product variants

Dimension	Colour	Light source	Lumen	Class	Lighting control
Ø 175	Black	1x100W E27	-	1	-
Ø 250	White	1x60W E27	2413	II	Dali
Ø 400		LED 3000-1800K D2W 41W	2604		Phase dimming (mains dimm)
Ø 550		LED 3000K 41W	2929		Wireless bluetooth
			3160		



Design

Mads Odgård

Weight

Min: 0.647 kg Max: 5.438 kg

Dimensions


Ø 175, Ø 250, Ø 400, Ø 550

Finish


Black, White

Light distribution diagrams






Isolux



Polar



Spare parts & accessories



Above

Product	Variant number
CANOPY BLACK 2-PART, TOPHAT ®	5749329021
ABOVE 250 PEND ANTI-GLARE SHADE MAT	5741910483
ABOVE 400/550 PEND ANTI-GLARE SHADE MAT	5741910496

